



主要信息

产品系列	Preventa安全检测
产品类型	安全开关
组件名称	XCSB
设计	工业的
材料	金属
操纵头类型	键控转塔头
触点类型	3 NC
触点动作	慢中断，同时
电缆进线孔	1带孔进线 适用 M20 x 1.5
电缆外径	7...13 Mm
电气连接	端子，夹紧力: 1 x 0.5...2 x 1.5 mm ² 带有或不带电缆末端
极数	3
有关锁的描述	带有执行器锁定装置，通过按钮进行解锁
本地信号指示	没有

补充信息

强制打开	带NC触头
机械寿命	600000 次
最小制动速度	0.01 M/S
最大操动速度	0.5 M/S
额定工作电流 [Ie]	6 A 在...上 120 V, AC-15, A300 符合 EN/IEC 60947-5-1 3 A 在...上 240 V, AC-15, A300 符合 EN/IEC 60947-5-1 0.55 A 在...上 126 V, DC-13, Q300 符合 EN/IEC 60947-5-1 0.27 A 在...上 250 V, DC-13, Q300 符合 EN/IEC 60947-5-1
约定封闭发热电流 [Ithe]	10 A
额定绝缘电压 [Ui]	300 V 符合 UL 508 500 V 符合 EN/IEC 60947-1 300 V 符合 CSA C22.2 No 14
额定冲击耐受电压 [Uimp]	6 KV 符合 EN/IEC 60947-5-1
短路保护	10 A 熔丝管 类型 gG (gl)
插片强制抽出 rtc	1500 N
Minimum actuator force for extraction	20 N
最大操作频率	10 次/分钟 用于最高耐用性
安全等级	可以达到 4 类 带相应监控系统与正确接线 符合 EN/ISO 13849-1 可以达到 PL = e 带相应监控系统与正确接线 符合 EN/ISO 13849-1 可以达到 SIL 3 带相应监控系统与正确接线 符合 EN/IEC 61508
安全可靠的数据	B10d = 5000000 价值由20年生命时间确定，受机械或接触磨损限制
本体材料	Zamak
头部材料	Zamak
深度	44 Mm
高度	114 Mm
宽度	52 Mm
产品重量	0.475 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

环境

符合标准	EN/ISO 12100 EN/IEC 60947-5-1 CSA C22.2 No 14 EN 1088/ISO 14119 EN/IEC 60204-1 UL 508
产品认证	CSA UL
保护处理	TC
运行温度	-25...70 °C
贮存环境温度	-40...70 °C
抗振动	5 gn (f= 10...500 Hz) 符合 IEC 60068-2-6
抗冲击	10 gn 适用 11 ms 符合 IEC 60068-2-27
电击保护级别	级别 I 符合 EN/IEC 61140
IP 保护等级	IP67 符合 EN/IEC 60529 and EN/IEC 60947-5-1

可持续性

产品类型	Green Premium 产品
REACH法规	REACH 声明
欧盟ROHS指令	Pro-active compliance (Product out of EU RoHS legal scope) 欧盟ROHS声明
无汞	是
RoHS 豁免信息	是
环境披露	产品环境文件
流通资料	无需具体的回收操作
加州 65 号提案	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

合同保修

保修单	18 months
-----	-----------